S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
1.	Computer	Tower Computer  • 11th Generation Intel® Core™ i5-11400 (12 MB Cache, 6 Core, 12 Threads, 2.6 GHz to 4.4 GHz, 65 W)  • 8 GB, 1 x 8 GB, DDR4, 2666 MHz for Intel® Pentium® and 10th Generation Intel® Core™ i3/i5 processors, 3200 MHz for 11th Generation Intel® Core™ i5/i7 processors  • Intel® UHD Graphics 730 for 11th Generation Intel® Core™ i5-11400 processors  • 3.5-inch, 1 TB, 7200 RPM, SATA, HDD  • M.2 2280, 256 GB, PCIe NVMe Gen3 x4, Class 40 SSD  • Ports  2 DisplayPort 1.4 ports 1 VGA Port/DisplayPort 1.4 Port/HDMI 2.0b Port/ USB  • 8x DVD+/-RW  • 300 W PSU or above  • With Original Brand Wired Multimedia Keyboard & Optical Mouse  • Black, LED IPS 24" Full HD (1080p) 1920 x 1080 at 60 Hz Display  Screen Coating Anti-Glare  • Input Connectors  Power connector 1 X VGA 1 X HDMI 1.4 1 X Display Port With Power and HDMI/Display Port/VGA Cable • 3 Years Hardware warranty with on-site service.  • Quoted brand must have presence in Pakistan for last 5-10 years.  • Year of Establishment/Certificate of Incorporation must be attached.	International Recognized Brands Dell/HP Or Equivalent	236Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		<ul> <li>Vendor should have Tier One GOLD partner.</li> <li>Principal register offices locally Services support/parts depot available in Pakistan</li> <li>Proof that the equipment is brand new and current year manufactured which should be verify able by the bill of landing and with the OEM.</li> <li>With Complete Brochure and Full Technical Specifications.</li> </ul>						
2.	All in One Printer	Printing specifications  Print technology Laser Duplex printing Automatic (standard) Print resolution (best) Up to 1200 x 1200 dpi Maximum print area (metric) 214 x 356 mm Monthly duty cycle Up to 30,000 pages Print languages, PCL5c; PCL6; PS; PCLm; PDF; URF.  Jet Intelligence cartridges, Duplex printing  Scan  Technology CIS Scan speed (normal) Up to 15 ppm Scan resolution, hardware  Up to 300 x 300 dpi (color and mono, ADF); Up to 600 x 600 dpi (color, flatbed); Up to 1200 x 1200 dpi (mono, flatbed) Levels of grayscale 256 Bit depth 24-bit Duplex ADF scanning No Maximum flatbed scan size (metric) 215.9 x 297 mm Minimum ADF scan size (metric) 148.5 x 210 mm,5.85 x 8.27 in Maximum ADF scan size (metric) 215.9 x 297 mm  Connectivity Ports 1 Hi-Speed USB 2.0; 1 Ethernet 10/100Base-TX  Copier settings Number of Copies; Lighter/Darker; Optimize; Paper; Multi-Page Copy; Collation; Draft Mode Maximum number of copies Up to 99 copies Copy reduce / enlarge 25 to 400% Copy speed (black, normal)  Up to 30 cpm (Letter), 28 cpm (A4) Copy resolution 600 x 600 dpi Memory 256 MB  Mobile printing ePrint; AirPrint 1.5; Google Cloud Print 2.0  Network protocols  TCP/IP: IPv4; IPv6; IP Direct Mode; LPD; SLP; Bonjour; WS-Discovery; BOOTP/DHCP/AutoIP; WINS; SNMP v 1/2/3; HTTP/HTTPS	International Recognized Brands HP/Canon Or Equivalent	23 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Paper handling Input capacity Up to 260 sheets priority tray (envelopes) Up to 10 Output capacity Up to 150 sheets A4 Media sizes supported Letter; Legal Paper (laser, plain, photo, rough, vellum), envelopes, labels, cardstock, postcards Media weight supported 60 to 163 g/m² Paper handling - ADF Automatic document feeder capacity 35 sheets of 75.2 g/m² (20 lb) Paper handling - duplexer Recommended media weight, duplex (metric) 60 to 105 g/m² Media sizes, duplex (metric) A4 Media sizes, Power Energy savings feature technology Auto-On/Auto-Off technology Power supply 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz/50 Hz, 5.9 A; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 60 Hz/50 Hz, 3.3A Power consumption 475 watts (active printing), 4.5 watts (ready), 1.0 watts (sleep), 0.8 watts (Auto Off/Wake on USB, enabled at shipment) Warranty One-year limited warranty						
3.	Color Printer	Color Printer Print speed Up to 29 ppm First page out (ready) black As fast as 9.3 sec First page out (ready) color As fast as 10.9 sec Resolution (black) Up to 600 x 600 dpi Resolution (color) Up to 600 x 600 dpi Resolution technology Monthly duty cycle Up to 55,000 pages Recommended monthly page volume 900 to 4,800 Pages	International Recognized Brands HP/Canon Or Equivalent	03 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Print Technology Laser Display 2.658" diagonal Color TFT-LCD back-lit (960 (H) x 240 (V)) Processor speed 800 MHz Number of print cartridges 4 (1 each black, cyan, magenta, yellow) Paper trays 3 Connectivity standard 1 Hi-Speed USB 2.0; 1 Host USB; 1 Gigabit Network Ready Standard (built-in Gigabit Ethernet) Duplex printing Automatic (default) Warranty One-year						
4.	Network Rack	Network Cabinet	International /Local Recognized Brands	24Nos				
5.	Network Switch	Layer 2 Gigabit  The Access Switch should have 24xGE RJ 45+ interfaces. Switch must have 4xGE SFP ports for uplink. VLAN support Trunk ports Spanning Tree Protocol Ac power Supply 3 years hardware replacement Warranty 24/7 support Web Based Managed Switch SFP Transceiver Qty=24 Single Mode 1XGE SFP Transceiver with 3 Years Hardware Replacement Warranty Note. Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey	International Recognized Brands Cisco Or Equivalent	12 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
6.	Network Cable Box	<ul> <li>Ethernet Pure Copper Cable Roll with installation</li> <li>Face Plate with Back Box and Cat 6 I/O Qty=150</li> <li>Connectivity of 25 Access points with Switches</li> <li>3 Meter Patch Cords pure Copper 23 AWG standard Qty=200</li> <li>Installation of Switches and Access points</li> <li>Cat6 RJ45 Connector Box Qty=06</li> <li>Note.</li> <li>Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey solution and quoted by single bidder</li> </ul>	International Recognized Brands	19 Nos				
7.	Laptop	Processor  11th Generation Intel® Core™ i5-1145G7 (8 MB Cache, 4 Core, 8 Threads, 2.60 GHz to 4.40 GHz, 15 W)  Operating System  Not Required  Video Card  Integrated: Intel® UHD Graphics Intel® Iris® Xe Graphics  Memory  8 GB, 1 x 8 GB, DDR4, 3200 MHz  Internal storage  M.2 2230, 256 GB, PCIe NVMe Gen3 x4, Class 35 SSD  Keyboard  Black, English US, backlit keyboard with optional fingerprint reader  Camera  720p at 30 fps HD camera, single integrated microphone 720p at 30 fps HD + IR camera, dual-array microphone Color  Black/Silver  Display 15.6-inch, FHD 1920 x 1080, 60 Hz, anti-glare, nontouch, 45% NTSC, 250 nits, wide-viewing angle Audio and Speaker	International Recognized Brands Dell/HP Or Equivalent	14 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Wireless technologies As per Installed Ports and Connectors 1 USB 3.2 Gen 2x2 Type-C port with Display Port alt mode/Power Delivery 2 USB 3.2 Gen 1 Type-A port 1 USB 2.0 port 1 HDMI 1.4a port 1 RJ-45 Ethernet port 1 universal audio port 1 power adapter port Slots 1 uSD 3.0 card slot 1 uSIM slot (WWAN only) 1 wedge-shaped lock slot Dimensions Height: 18.06 mm (0.71") x Width: 361 mm (14.2") x Depth: 240.9 mm (9.5") Starting Weight (Minimum): 1.79 kg (3.95 lb) <sup>i</sup> Battery 3-cell, 41 WHr Polymer,ExpressCharge™, Integrated 4-cell, 54 WHr Polymer,ExpressCharge™, Integrated Warranty 3-years warranty With Complete Brochure & Full Technical Specification • Original Carrying Case/Bag for 15.6" Laptop						
8.	Projector	LCD, 4100 lumens, XGA  Lamp and filter replacement cycle of up to 10,000 hours  Quiet 28 dB Operation for Distraction  16,000:1 contrast ratio  Power Supply AC100-240V 3.5A 50/60 Hz Power Consumption 300W 6W when Standby mode set to Normal, 0.5W when Standby mode set to Eco*1  LCD Panel Size 16.0 mm (0.63 inches) diagonal (4:3 aspect ratio) Pixel 786,432 (1,024 x 768) x 3, total of 2,359,296 pixels  Lense Manual zoom (1.2x), manual focus F 1.6- 1.76, f 19.16-	International Recognized Brands Sony/Panasonic Or Equivalent	32Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		23.02 mm						
1		<b>Throw Ration</b> 1.48- 1.78:1, Lamp 230 W UHM lamp						
		Lamp/Filter*2 Replacement Cycle Normal: 5,000hrs / Eco1: 6,000hrs / Eco2: 10,000hrs <b>Screen Size</b> 30-300 inches (0.76 -7.62 m) diagonally, 4:3 aspect ratio Colors Full color (16,777,216 colors) Brightness*3						
		Lumens 4,100 lumens (lamp power: normal)						
		<b>Resolution</b> 1,024 x 768 pixels (Input signals that exceed this resolution will be converted to 1,024 x 768 pixels.)						
		<b>Keystone Correction</b> Range Vertical: ±30°, horizontal: ±15°						
		Installation Ceiling/floor, front/rear (menu selection)						
		Built-in Speaker   Output Power 10 W (monaural) x 1						
		Terminals						
		HDMI In HDMI 19-pin x 1, HDCP and Deep Color compatible Audio signal: linear PCM, Computer (RGB) 1 In D-sub HD 15-pin (female) x 1, Computer (RGB) 1 In   R, G, B R, G, B: 0.7 Vp-p, 75 ohms; Computer (RGB) 1 In   Y, PB (CB), PR (CR) Y: 1.0 Vp-p (including sync signal), 75 ohms PB, Computer (RGB) 1 In   S-VideoY: 1.0 Vp-p; C: 0.286 Vp-p, 75 ohms						
		Computer (RGB) 2 In D-sub HD 15-pin (female) x 1, Computer (RGB) 2 In   R, G, B R, G, B: 0.7 Vp-p, 75 ohms; Monitor Out D-sub HD 15-pin (female) x 1, Monitor Out   R, G, BR, G, B: 0.7 Vp-p, 75 ohms; Video In Pin jack x 1, 1.0 Vp-p, 75 ohms, Audio In 1 M3 (L, R) x 1, 0.5 Vrms, Audio In 2 Pin jack x 2 (L, R x 1), 0.5 Vrms, Audio Out M3 (L, R) x 1 (monitor out: 0-2.0 Vrms, variable), Serial In D-sub 9-pin (female) x 1, for external control (RS-232C compliant), LAN RJ-45 x 1, for network connection, compliant with PJLink <sup>TM</sup> , 100Base-TX/10Base-T						
		<b>Screen</b> Size 120" Inch 16:9 Manual with Wall Mount Hanging Clips						
		Cables 15 Meter VGA&HDMI Cables,						
		KIT Projector Celling mount Hanging Complete Set						
		Warranty 1-year warranty						
9.	Server Machine/Rack	<ul> <li>Server Form Factor: 1U or above</li> <li>Processor: 2 x Intel Xeon Ice lake Series Processor Gold 12 Core or more,</li> </ul>	International Recognized Brands	04 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
	Servers	<ul> <li>Memory:128GB RAM,</li> <li>SSD: 2 x 480 GB RI SSDs</li> <li>Card: 32GB Raid-1 SD Card</li> <li>Remote Access: Integrated Remote Access 1G port(with CAT6 15m branded cables) with Enterprise License,</li> <li>Network Adapter: 2 x Dual port 10Gb Network Card SFP+ Transceivers with OM4 LC/LC 15m Cable, 4 x 1Gb Ethernet with CAT6 15m branded Cables, 16Gb 2-Port FC Card with Transceivers,</li> <li>RAID controller: 2Gb Supporting RAID Level 0,1,5,6,10,50,60</li> <li>Power Supply: 800watts Dual, Hot-plug, Redundant Power Supply (1+1)</li> <li>Warranty: 3 years 24x7 Pro Support</li> <li>Important Note:</li> <li>Servers, Storage and Racks must be of same brand.</li> <li>Vendor must be Tier 1 and Authorized Service delivery partner from last 3 years. (Documentary proofed from Principal required)</li> <li>MAL from OEM is mandatory</li> <li>Hands on training of all active equipment during Deployment</li> <li>Quoted brand must have presence in Pakistan for last 5-10 years.</li> <li>Serial No 9,10, 16b will be a part of turnkey solution and quoted by single bidder.</li> </ul>	Dell/HP/ or Equivalent					
10.	Enterprise Storage	<ul> <li>SAN Storage = 01</li> <li>Rack Mounted Mid-Range SAN Storage</li> <li>(Supports SSD/SAS HDD/ NL-SAS)</li> <li>Controller: Dual Controller SAN Storage</li> <li>The storage array should support dual, redundant, hotpluggable, active-active array controllers for high performance and reliability</li> <li>SSD: 2 x 1.92TB RI SSD</li> <li>Hard Disk: 14x 1.2TB 10K RPM SAS 12Gbps or higher</li> <li>Storage shall be scalable to minimum of 240 number of</li> </ul>	International Recognized Brands  DELL/Hitachi/Brocade or Equivalent	02 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		SAS SFF drives.						
		<ul> <li>Storage system shall support Enterprise SAS spinning drives, SSD and near line SAS/7.2K RPM drives.</li> </ul>						
		<ul> <li>Offered storage array shall also have support for FIPS 140-2 validating self-encrypted drives.</li> </ul>						
		<ul> <li>Offered Storage shall also have optional support for Flash cache using SSD / Flash drives. Offered storage shall support at-least 8TB Flash Cache.</li> </ul>						
		<ul> <li>Multi-path and load balancing software shall be provided, if vendor does not support MPIO functionality of Operating system.</li> </ul>						
		SAN Controller Cache: 12GB Per Controller or higher						
		• Ports: 4 x 16G FC ports each controller						
		• FC Cables: 8 x 5m OM4 LC/LC FC cables						
		Power Supply: Redundant Power Supply						
		• Warranty: 3 years 24x7						
		NAS (Network Attached Storage) = 01						
		NAS should be rack mounted with a form factor of 1U or Above						
		<ul> <li>One hexa Core Intel 1.9 GHz Intel Xeon Bronze 3204 or higher. NAS Controller shall be scalable to dual number of physical processors.</li> </ul>						
		<ul> <li>16GB Dual Rank x8 DDR4 - 2933 CAS 21-21-21 RAM or higher, scalable to 192GB DDR4 RAM</li> </ul>						
		<ul> <li>Shall be supplied with minimum of 4 x 2TB drives in Raid 1+0. Offered NAS controller shall have support for higher capacity drives of 8TB.</li> </ul>						
		Offered NAS should have redundant Power supplies						
		<ul> <li>Shall have more than 200TB external disk scalability using SAS / SAS -NL drives by providing associated hardware whenever required.</li> </ul>						
		<ul> <li>Minimum 4 x 1Gbps with CAT6 15m branded cables, 2 x 10G SFP+ with Transcievers and OM4 LC/LC 15m</li> </ul>						

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
11.	Hardware Firewall	ethernet ports.  ISCSI, FTP, FTPS, CIFS/SMB 3.1.1, HTTP, HTTPS, NFS 4.1,etc.  Offered NAS shall support Raid 0, Raid 1, Raid 1+0, Raid 5 and Raid 6 for additional disk enclosures.  Microsoft Windows Storage IOT 2019 - 64 bit edition (NAS optimized) including powered OS drivers  Offered NAS shall have block based De-duplication which can be enabled for all required volumes  Shall have web based interface to manage and monitor system health, capacity, performance, hardware events, quotas, snapshots, authentication and network services  Warranty: 3 years 24 x 7  Quoted brand must have presence in Pakistan for last 5-10 years. Serial No 9,10,16b will be a part of turnkey solution and quoted by single bidder  Latest Hardware Firewall With Licenses  Firewall Throughput  Minimum Firewall Throughput 38 GBps  Next Generation Firewall Throughput 8 Gbps  IPS throughput 8 Gbps or more  IPSec VPN Throughput 3Gbps or more  Minimum of 12 Million Concurrent session  Firewall should be able to work without license in routing mode.  Network Ports and Protocol  x 1 GE Copper (RJ45) Interfaces, 2XGE SFP Ports,  2 port 10Gbps SFP Fiber Module.  4X10GE Fiber module option for future use  Fully Support Dynamic Routing Protocols (OSPF, BGP), PBR.  Multi Wan Link Load Balancing  Interactive Traffic Monitoring and Management  Traffic Shaping, Bandwidth Monitoring and QOS	International Recognized Brands Cisco/Fortinet/Sonicwall or Equivalent	02 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
12.	Manageable L3 48 Port Switch	<ul> <li>Reporting</li> <li>Real time Graphical visibility chart of each Source IP connected to the destination IP and type of traffic. X</li> <li>User Friendly GUI Interface</li> <li>Detail On-Box Reporting and logging at least for 3 months License Subscription</li> <li>Must Have Security Subscriptions (IDS/IPS, Anti-Virus, Web/Content Filter, Application Blocking.)</li> <li>Firewall must be rated in NSS Lab Report attached Report (Last 3 years)</li> <li>Firewall must have capability for Web Application Firewall for protection of servers by using license.</li> <li>300 SSL VPN license.</li> <li>3 years Warranty and support 24/7</li> <li>Note.</li> <li>Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey solution and quoted by single bidder</li> <li>Slot Chassis Or Stackable Switch</li> <li>Ports</li> <li>Switch should have 48x 10 GE SFP+ interfaces.</li> <li>Switch must have 6x40GE QSFP+ ports for uplink.</li> <li>Switch must support one modular slot for future expansion.</li> <li>Flash 2 Gb</li> <li>RAM 8 GB</li> <li>Switch must have minimum 1.8Tbps switching capacity or Higher</li> <li>Switch must have minimum 1.2Bpps forwarding capacity or Higher</li> <li>Switch must have stack cable and stack Supported.</li> <li>Switch must support one modular slot for future expansion.</li> <li>L3/L2 Features</li> <li>Fully Managed Layer 3</li> <li>Minimum 30,000 MAC Address Support</li> <li>Port Loop Detection, VLAN support</li> </ul>	International Recognized Brands Cisco Or Equivalent	02 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		<ul> <li>MAC binding, Link Aggregation Spanning tree protocol.</li> <li>RIP, OSPF v2/v3, BGP4, BGP4+ and GRE support, Virtual Interfaces, Routed interfaces.</li> <li>SDN Open Flow 1.3 support</li> <li>Open Flow with Hybrid Modes</li> <li>Support or able to Operate with Open Day light Controller.</li> <li>MAC authentication, 802.1X authentication</li> <li>BPDU Guard Root Guard support</li> <li>Authentication , authorization and Accounting support</li> <li>Layer 3/Layer 4 ACL</li> <li>Switch must support IPV4 and IPV6</li> <li>Management</li> <li>User Friendly GUI Management</li> <li>Management via telnet ,SSH and console</li> <li>TFTP Server support</li> <li>SNMP v1,v2 and v3 support</li> <li>Industry standard CLI support</li> <li>Industry standard CLI support</li> <li>Dual Power Supply</li> <li>SFP Modules</li> <li>Single Mode 10GE SFP+ Modules= Qty 50</li> <li>Stack Cable</li> <li>Stack Cable for Stack Connectivity= Qty 1</li> <li>Fiber Patch Cords 10GE Supported</li> <li>Duplex Optical Fiber Single Mode Patch Cord SC/LC to LC 10GE Supported (3Mtr)= 40</li> <li>Duplex Optical Fiber Single Mode Patch Cord LC to LC 10GE Supported (3Mtr)=10</li> <li>Duplex Optical Fiber Single Mode Patch Cord SC to LC 1GE Supported (3Mtr)=24</li> <li>Quoted brand must have presence in Pakistan for last 5-10 years. Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey solution and quoted by single bidder</li> </ul>						
13.	Manageable L3	24 port Switch Cisco or Equivalent Ports	International	10 Nos				
	24 Port Switch	Fully Managed Layer 3 Switch	Recognized Brands					

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		<ul> <li>The Access Switch should have 24x 10/100/1000 RJ 45 interfaces.</li> <li>Switch must have 4x10GE SFP+ ports for uplink.</li> <li>Switch must have minimum 128Gbps switching capacity or Higher</li> <li>Switching performance 95Mpps or Higher</li> <li>RAM 1 GB</li> <li>Flash 2 GB</li> <li>Minimum15000 MAC Address Support.</li> <li>Protected ports Support</li> <li>L3/L2 Features</li> <li>Port Loop Detection, VLAN support</li> <li>MAC binding, Link Aggregation Spanning tree protocol.</li> <li>RIP, OSPF v2/v3 Support.</li> <li>Virtual Interfaces, Routed interfaces.</li> <li>VRRP support</li> <li>SDN Open Flow 1.3 support</li> <li>Open Flow with Hybrid Modes</li> <li>Support or able to Operate with Open Day light Controller.</li> <li>MAC authentication, 802.1X authentication</li> <li>BPDU Guard Root Guard support</li> <li>Authentication , authorization and Accounting support</li> <li>Switch must support IPV4 and IPV6</li> <li>Management</li> <li>User Friendly GUI Management</li> <li>Management via telnet ,SSH and console</li> <li>SCP ,TFTP Server support</li> <li>SNMP v1,v2 and v3 support</li> <li>NTP, DHCP server and DHCP relay support</li> <li>Industry standard CLI support</li> <li>Industry standard CLI support</li> <li>Industry standard CLI support</li> <li>Operated broad must have presence in Pakieten for lest 5, 10 years</li> </ul>	Cisco Or Equivalent					
		Quoted brand must have presence in Pakistan for last 5-10 years.  Note.  Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey solution and quoted by single bidder.						

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
14.	Fiber Connectivity	Fiber Connectivity For Data Center  96 Core Armored Cable 1500 Meter  96 Core Armored Fiber Cable  Single Mode Cable 10GE Supported  8 Core Armored Cable 1100 Meter  Single Mode Cable 10GE Supported  96 Port ODF Qty 02 Nos  96 Port ODF metal Body ODF  Single Mode 10GE Supported Pigtail and adopter  8 Port ODF Qty 22 Nos  8 Port ODF metal Body ODF  Single Mode 10GE Supported Pigtail and adopter  HDPE Pipe 2000 Meter  HDPE Pipe 2000 Meter  HDPE Pipe-2 Inch diameter with 5mm thickness  Joint Qty 24 Nos  Fiber Joint Box 96 Core  Pipe and Fiber Laying Main Hole Qty30  GI Cable tray With Cover 3"x2"With Fixing Material=250 Feet  GI Flexible 2"=50 Feet  Hard Surface Trench With Back Filling Depth 3' With Marking  Tape=300 meter  Soft Surface Trench With Back Filling Depth 3' With Marking  Tape=1300 meter  Manhole as per specifications 3'x3'x4' With Cover=30  Road Cutting and Bore & Repair with same material=20 Meter  Fiber Cable Laying=2600 meter  Splicing and With OTDR Testing=2500 splice  Note.  Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey solution and quoted by single bidder	International Recognized Brands	O1 Job				
15.	Wi-Fi Controller	<ul> <li>Wi-Fi Controller= 01</li> <li>Minimum 150 Access points Support</li> <li>Minimum 4000 Concurrent Clients</li> <li>Minimum 256 SSID support</li> <li>WPA, WPA2 support</li> <li>Software Queues per client</li> <li>Rate Limiting</li> <li>Customize Dashboard</li> <li>Guest Networking</li> </ul>	International Recognized Brands Cisco Or Equivalent	01 Job				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		<ul> <li>Real Time Admission Control</li> <li>Quality of service with WLAN prioritization, band steering and airtime fairness</li> <li>RADIUS, LDAP, Active directory Supported</li> <li>Integrated captive portal</li> <li>STA location Service</li> <li>AC Power Supply</li> <li>1 year Warranty</li> <li>Integrated DHCP Server</li> <li>2X1 GE Ethernet Port</li> <li>Wireless Standard 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.11r, 802.11t, 802.11v,</li> <li>License for 25 or Above Access Points</li> <li>Transceiver</li> <li>Ethernet Transceiver= Qty 2</li> <li>Access Point Mid Range = Qty 20</li> <li>Controller Based IEEE 802.11a/b/g/n/ac/ax</li> <li>2.4GHz &amp; 5 GHz channels</li> <li>2x2:2802.11ac/ax</li> <li>2x2 SU MIMO</li> <li>2X2 MU MIMO</li> <li>Min 250 Concurrent users</li> <li>Throughput 2.4GHz support 500Mbps and 5GHz support 1200Mbps or Higher</li> <li>Channelization of 20MHz, 40MHz, 80MHz and 160MHz</li> <li>IPv4, IPv6 Support</li> <li>WPA-PSK, WPA-TKIP, WPA2 AES, WPA3-Personal, WPA3- Enterprise, 802.11i, Dynamic PSK, OWE · WIPS/WIDS</li> <li>NAT DHCP support</li> <li>15 SSID per AP</li> <li>User Based Rate Limiting</li> <li>POE 802.3af and 802.3at support</li> <li>EN 60950-1 Safety certified</li> <li>EN 60601-1-2 Medical certified</li> <li>VLAN support</li> <li>Dynamic Pre-Shared Key Support</li> </ul>						

ame of quipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
	<ul> <li>Direct Multicast</li> <li>Smart Roam</li> <li>GRE, Soft-GRE</li> <li>3 year warranty</li> <li>Access Point High Range=05</li> <li>Controller Based IEEE 802.11a/b/g/n/ac/ax</li> <li>2.4GHz &amp; 5 GHz channels</li> <li>4x4 802.11ac/ax</li> <li>Min 500 Concurrent users</li> <li>Total Throughput 2800 Mbps</li> <li>Channelization of 20MHz, 40MHz, 80MHz and 160MHz</li> <li>IPv4, IPv6 Support</li> <li>WPA-PSK, WPA-TKIP, WPA2 AES, WPA3-Personal, WPA3-Enterprise, 802.11i, WIPS/WIDS</li> <li>NAT DHCP support</li> <li>16 SSID per AP</li> <li>User Based Rate Limiting</li> <li>POE 802.3af and 802.3at support</li> <li>EN 60950-1 Safety</li> <li>EN 60601-1-2 Medical</li> <li>EN 62311 Human Safety/RF Exposure</li> <li>VLAN support</li> <li>Direct Multicast</li> <li>Dynamic Pre-Shared Key Support</li> <li>Smart Roam</li> <li>GRE, Soft-GRE</li> <li>3 year warranty</li> <li>Layer 2 Gigabit POE Switch Qty 22</li> <li>The Access Switch should have 8xGE RJ 45+ interfaces.</li> <li>Switch must have 2xGE SFP ports for uplink.</li> <li>VLAN support</li> <li>Trunk ports</li> <li>Spanning Tree Protocol</li> <li>Ac power Supply</li> </ul>						

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		<ul> <li>75 Watt POE Total Budget</li> <li>30 Watt Per Port Budget</li> <li>Note.</li> <li>Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey solution and quoted by single bidder</li> </ul>						
16.	Server Racks	4pcs cooling fans on the top cover, based on the depth (D600mm with 2pcs fans, D800mm & D1000mm with 4pcs fans).  1-3pcs fixed shelves included, depends on different height Cage nuts 300 Pieces included, depends on different height (floor standing below 27U with 20sets screws, 32U & 37U with 30sets screws, 42U & 47U with 40sets screws).  Back Door 4 Fans  LED indicators for ground and surge detection  Qty=5 (6 Ports PDU)  Rack mount cable management panel  Network rack patch panel  Reusable Cable Ties Microfiber Cloth Hook and Loop  a. Server Racks (For Network Communication) = 02  2 x 42U Server Rack with  2 x 16amp PDU with 10 or more C13 connectors in each rack  Note.  Serial No 4,5,6,11,12,13,14,15,16a will be a part of turnkey solution and quoted by single bidder.  b. Server Racks (For Server/Storage) = 02  2 x 42U Server Rack with 8 Port KVM with accessories and cables, 2 x 16amp PDU with 10 or more C13 connectors in each. Foldable LCD Console kit  Note.  (Must be of same brand as per Server/Storage)  Serial No 9,10,16b will be a part of turnkey solution and quoted by single bidder	International Recognized Brands	04 Nos				
17.	Scanner	Scanner Resolution Up to 600 x 600 dpi (color and mono, ADF); Up to 1200 x 1200	International Recognized Brands	05 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		dpi (color and mono, flatbed) Up to 600 dpi (color and mono, ADF); Up to 1200 dpi (color and mono, flatbed) Optical or above Scan speed: Up to 25 ppm/50 ipm Weight 12.3 lb Supported operating systems Windows 10 (32-bit/64-bit), Windows 8.1 (32-bit/64-bit), Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit); Mac OS X Mavericks 10.9, OS X Yosemite 10.10 ENERGY STAR ENERGY STAR ENERGY STAR® 3.0 certified Warranty One-year limited hardware warranty; 2-line LCD; 5 buttons (Simplex/Duplex, Power, Cancel, Back and Tools/Maintenance) Bit depth 24-bits external 48-bits internal Maximum document scan size 8.5 x 122 in Scannable media types Paper (banner, inkjet, photo, plain), envelopes, labels, cards (greeting, index) Input type Flatbed, ADF Auto document feeder Standard, 50 sheets or Above Connectivity	HP or Equivalent					
18.	Printers	USB 2.0 and USB 3.0  PRINT SPEED BLACK (ISO, A4)  Normal: Up to 38 ppm (default); Up to 40 ppm (HP High Speed)  FIRST PAGE OUT (READY)  Black: As fast as 6.3 sec  FIRST PAGE OUT (SLEEP)	International Recognized Brands HP/Canon Or Equivalent	04 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Black: As fast as 8.8 sec						
		PRINT QUALITY BLACK (BEST)						
		Fine Lines (1200 x 1200 dpi)						
		PRINT RESOLUTION TECHNOLOGIES						
		HP FastRes1200, HP ProRes1200, Economode						
		DUTY CYCLE (MONTHLY, A4)						
		Up to 80,000 pages RECOMMENDED MONTHLY PAGE VOLUME						
		750 to 4,000 [4]						
		PROCESSOR SPEED						
		1200 MHz						
		PRINT LANGUAGES						
		HP PCL 6, HP postscript level 3 emulation, PDF, URF, PWG Raster						
		DISPLAY						
		2-line backlit LCD graphic display						
		CONNECTIVITY, STANDARD						
		1 Hi-Speed USB 2.0; 1 host USB at rear side; Gigabit Ethernet 10/100/1000BASE-T network; 802.3az(EEE)						
		MEMORY						
		256 MB						
		MAXIMUM MEMORY						
		256 MB						
		INTERNAL STORAGE						
		None						
		PAPER HANDLING OUTPUT, STANDARD						
		150 sheet output bin						
		PAPER HANDLING INPUT, OPTIONAL						
		Optional third 550 sheet tray						
		PAPER HANDLING INPUT, STANDARD						
		100 sheet multipurpose Tray 1, 250 sheet input Tray 2						
		MAXIMUM OUTPUT CAPACITY (SHEETS)						
		Up to 150 sheets						
		DUPLEX PRINTING						

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Automatic (default)						
		MEDIA SIZES SUPPORTED  Tray 1, Tray 2: A4; A5; A6; B5 (JIS); B6 (JIS); 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm); 10 x 15 cm; Oficio (216 x 340 mm); Postcards (JIS single, JIS double); Envelopes (DL, C5, B5); Optional Tray 3: A4; A5; A6; B5 (JIS); B6 (JIS); 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm); 10 x 15 cm; Oficio (216 x 340 mm); Postcards (JIS single, JIS double); Automatic duplexer: A4; B5; 16K (195 x 270 mm, 184 x 260 mm; 197 x 273 mm); Oficio (216 x 340 mm)  MEDIA SIZES, CUSTOM						
		Tray 1: 76 x 127 to 216 x 356 mm; Tray 2, optional Tray 3: 100 x 148 to 216 x 356 mm						
		MEDIA TYPES						
		Paper (plain, EcoFFICIENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough); Envelopes; Labels						
		MEDIA WEIGHT, SUPPORTED						
		Tray 1: 60 to 200 g/m <sup>2</sup> ; Tray 2: Optional 550 sheet; Tray 3: 60 to 120 g/m <sup>2</sup>						
		POWER 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)						
		POWER CONSUMPTION						
		495 watts (Active Printing), 5.5 watts (Ready), 0.5 watts (Sleep), 0.5 watts (Auto Off/Wake on LAN, enabled at shipment), 0.05 watts (Auto Off/Manual On), 0.05 (Manual Off) [8]						
		ECOLABELS						
		ENERGY STAR® qualified; EPEAT® Silver; CECP						
		SUSTAINABLE IMPACT SPECIFICATIONS						
		Mercury-free						
		BLUE ANGEL COMPLIANT						
		Yes, Blue Angel DE-UZ 205—only ensured when using Original HP supplies						
		OPERATING TEMPERATURE RANGE						
		15 to 32.5°C RECOMMENDED OPERATING HUMIDITY RANGE						

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
19.	Workstation PC	30 to 70% RH ACOUSTIC POWER EMISSIONS (READY) 2.6 B(A) [7] ACOUSTIC PRESSURE EMISSIONS BYSTANDER (ACTIVE, PRINTING) 54 dB(A) [7] MINIMUM DIMENSIONS (W X D X H) 381 x 357 x 216 mm [6] Without trays and covers not extended MAXIMUM DIMENSIONS (W X D X H) 381 x 781 x 241 mm [6] Without trays and covers not extended WEIGHT 8.56 kg PACKAGE DIMENSIONS (W X D X H) 443 x 274 x 464 mm PACKAGE WEIGHT 10.5 kg  Tower Workstation PC Processor Intel Xeon Processor W-2235 (6C, 3.8GHz 4.6GHz Turbo HT 8.25MB (130W)) DDR4-2933 RAM 32GB 2x16GB DDR4 2933MHz RDIMM ECC Memory Video Graphic Card NVIDIA Quadro P2000, 5GB, 4 DP HDD 3.5" 4TB 7200rpm SATA AG-Enterprise Hard Drive SSD for Boot M.2 512GB PCIe NVMe Class 40 Solid State Drive Optical Drive 16X Half Height DVD-ROM Network Cards 1Gbit NIC add-in card (PCIe- Intel) 3 Years Hardware Warranty with Onsite/In-Home Service after Remote Diagnosis	International Recognized Brands HP/Dell Or Equivalent	03 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		WLED Display Workstation Screen 3840 x 2160 at 60 Hz 27-inch LED Monitor With HDMI and Display Ports and Cables  1 x HDMI port version 2.0  1 x DisplayPort version 1.2  2 x High-Speed USB 2.0 downstream ports  2 x USB 3.2 Gen1 (5 Gbps) downstream ports  1 x USB Type-C (Alternate mode with DisplayPort 1.2, USB 3.2 Gen1 (5 Gbps) upstream port, Power Delivery PD up to 65 W)  Year of Establishment/Certificate of Incorporation must be attached.  Vendor should have Tier One GOLD partner.  Principal register offices and locally Services support/parts depot available in Pakistan  Proof that the equipment is brand new and current year manufactured which should be verify able by the bill of landing and with the OEM.  With Complete Brochure and Full Technical Specification						
20.	Ethernet patch cord	Cat-6 RJ45 1Meter patch cords (Multi Colors ) With Reusable Cable Ties Microfiber Cloth Hook and Loop	International Recognized Brands	500 Nos				
21.	Biometric Machine	Type Of Attendance System Fingerprint Attendance System Products Included Charger Battery Backup 6-8 hours Display Type TFT Touch Screen LanguageEnglish Connectivity Type Wired Communication TCP/IP,RS232/485 Installation Type Wall Mounted Power Supply 12 V 3A Memory Capacity 256 Flash, 64 M SDRAM Operating Temperature 45 Degree C Operating Humidity 20-80% Fingerprint Capacity 2000 Log Capacity 100000 Cpu And Memory ZK Multi-Bio CPU MHZ Hardware Platform ZEM600 Multi medium development Varification Time 2 sec Face Capacity 400	International Recognized Brands	01 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Camera High Resolution Infrared Camera Warantey 1 Years						
22.	Apple NLE iMac	NLE Apple iMac (27-inch iMac with Retina 5K display. 3.8 Ghz quadcore 7th generation Intel Core i5 processor, Turbo Boost up to 4.2GHZ 8GB 2400MHZ DDR42TB fusion Drive radeon Pro 580 with 8GB video memory	International Recognized Brands Apple Or Equivalent	01 Nos				
23.	8 Port switch	Gigabyte Switch 8 port With 1 Years Warranty	International Recognized Brands	01 Nos				
24.	Network Patch cord	3M Ethernet cable roll Cat-6	International Recognized Brands	01 Nos				
25.	Projector	White Brightness 12,000 ANSI Lumens / 8,000 Lumens (Eco) Color Brightness 12,000 Lumens CLO Resolution 1920x1200 Aspect Ratio 16:10 (WUXGA) Display Type 3 cm 3LCD Chips Color Processing 8-bit Video Modes 720p, 1080i, 1080p/60, 1080p/24, 1080p/50, 576i, 576p, 480p, 480i Data Modes MAX 1920x1200 Lamp Type Laser Phosphor Lamp Life 20,000 hours Lens Shift Horizontal & Vertical Digital Zoom Yes	International Recognized Brands	01 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Digital Keystone Horizontal & Vertical Projector Size 20 cm x 54 cm x 56 cm (HxWxD) Weight 28.0 kg Audible Noise 42 dB / 39 dB (Eco) Internal Speakers No Power 1,150 Watts 100V - 240V Connection Panel DVI Digital Input HDBaseT: RJ-45 HDMI 1.4 RGB In: BNC USB VGA In: Dsub-15pin VGA Out: Dsub-15pin Features Edge Blending Lens Memory Infinite Black Note. Part of Serial No 25,26,27,28 and quoted by single bidder						
26.	Projector Zoom Lens	Throw Ratio With VPL-FH500L: 2.62 to 3.36:1 With VPL-FX500L: 2.67 to 3.42:1 Lens Shift Range With VPL-FH500L: ± 113% V, ±63% H With VPL-FX500L: ± 96% V, ±64% H Note. Part of Serial No 25,26,27,28 and quoted by single bidder	International Recognized Brands	01 Nos				
27.	Mount For Projector	Projector mount with installation  Note.  Part of Serial No 25,26,27,28 and quoted by single bidder	International Recognized Brands	01 Nos				
28.	Projector Screen	Motorized projector screen 16'x12'	International	01 Nos				

S/No	Name of Equipment	Specifications	Required Brand	Quantity	Unit Price (w/o GST)	Total Price (w/o GST)	17% GST	G. Total (with GST)
		Note. Part of Serial No 25,26,27,28 and quoted by single bidder	Recognized Brands					
29.	NLE machine For Video Editing	NLE machine core i7, 10th Gen Or higher, 32GB RAM, 2TBx2 HD, with 6GB RTX 2060 graphics card, 700 PSU, keyboard, mouse & With IPS 24" LED Warranty 3 Years Onsite Year of Establishment/Certificate of Incorporation must be attached. Vendor should have Tier One GOLD partner. Principal register offices and locally Services support/parts depot available in Pakistan Proof that the equipment is brand new and current year manufactured which should be verify able by the bill of landing and with the OEM.	International Recognized Brands	01 Nos				

#### The University will enter into a contract with the successful vendor having the following terms & conditions.

- 1. Staff Training, Installation and Commissioning of IT Equipment.
- 2. Technical Support for 3 years.
- 3. Complete Installation of IT Equipment with required specification.
- 4. Educational/Academic Discounts also required where applicable.
- 5. Vendor Must Provide IT Equipment with Documentation/Manuals/Brochures/Diagrams/Designs.
- 6. Vendor Must Provide IT Equipment with Keys/User Name Passwords/Configuration Backup files.